



SPORTON LAB.

Certificate No: CB10003179

Report No.: EC132335

CERTIFICATE

- **EQUIPMENT: ICP DAS with Converter**
MODEL NO. : TPD-280 (Please refer to the following table)
APPLICANT : ICP DAS CO., LTD.

No. 111, Kuangfu N. Rd., Hukon Shiang, Hsinchu, Taiwan
303, R.O.C.



I HEREBY

CERTIFY THAT:

THE MEASUREMENTS SHOWN IN THIS TEST REPORT WERE MADE IN ACCORDANCE WITH THE PROCEDURES GIVEN IN **EUROPEAN COUNCIL DIRECTIVE 2004/108/EC**. THE EQUIPMENT WAS **PASSED** THE TEST PERFORMED ACCORDING TO **European Standard EN 55022:2006/A1:2007 Class A, EN 61000-3-2:2006, EN 61000-3-3:2008, EN 55024:1998/A1:2001/A2:2003 (IEC 61000-4-2:2008, IEC 61000-4-3:2008, IEC 61000-4-4:2004, IEC 61000-4-5:2005, IEC 61000-4-6:2008, IEC 61000-4-8:2009, IEC 61000-4-11:2004)**. THE TEST WAS CARRIED OUT ON **Mar. 25, 2011** AT **SPORTON INTERNATIONAL INC. LAB.**

Castries Huang
Castries Huang

Castries Huang



CB10003179

Report No.: EC132335

The model listed below is series model to TPD-280.

Main	Softwave	Diversity
TPD-280		2.8" touch HMI device with RS-485
TPD-283		2.8" touch HMI device with Ethernet
VPD-130		3.5" touch HMI device with RS-232/RS-485, USB, RTC, Rubber Keypad
VPD-130N		3.5" touch HMI device with RS-232/RS-485, USB, RTC
I-8212W		Industrial Quad-band 2G GSM/GPRS module
I-87024RW		4-channel 14-bit analog output module
I-87026PW		6-channel Analog Input, 2-channel Analog Output, 2-channel Digital Input and 2-channel Digital Output Module
I-87037W		16-channel Digital Output
I-87084W		4/8-channel Counter/Frequency/Encoder Module
I-7014D	DCON	Analog/Transmitter Input with LED Display
M-7014D	Modbus	Analog/Transmitter Input with LED Display
I-7024	DCON	4-channel 14-bit Analog Output Module
I-7024R	DCON	4-channel 14-bit Analog Output and 5-channel Digital Input Module
M-7024	Modbus	4-channel 14-bit Analog Output and 5-channel Digital Input Module
SG-770		7-channel Surge Protector
SG-785		The RS-485 pull-high/pull-low and termination resistors module
M-7059		8-channel 10-80 VAC Isolated Digital Input Module with 16-bit Counters
M-7059D		8-channel 10-80 VAC Isolated Digital Input Module with 16-bit Counters with LED
GPS-721		Remote GPS Receiver Module with 1 DO and 1 PPS outputs
DS-712		Device Server with 1-port RS-232
DS-715		Device Server with 1-port RS-422 / RS-485
PDS-755		1-Port RS-232 , 4-Port RS-485
PDS-755D		1-Port RS-232 , 4-Port RS-485 with LED
PDS-782-25		7-Port RS-232 , 1-Port RS-485
PDS-782D-25		7-Port RS-232 , 1-Port RS-485 with LED
NS-200AFC		Industrial 10/100 Base-T to 100 Base-FX Media Converter
NSM-208G		Unmanaged 8-Port Industrial 10/100/1000 Base-T Ethernet Switch
NSM-208AG		Unmanaged 8-Port Industrial 10/100/1000 Base-T Ethernet Switch With Power Input +12 ~ 48 VDC
iP-8411	C Language	Programmable Automation Controller 4 Slots
iP-8417	ISaGRAF	Programmable Automation Controller 4 Slots
iP-8811	C Language	Programmable Automation Controller 8 Slots

Main	Software	Diversity
iP-8817	ISaGRAF	Programmable Automation Controller 8 Slots

Please refer to user manual.